

AG800 EExd

50 litre/min 230v AC Fuel pump EEx D



AG800

The AG800 was primarily designed for use as a high flow flame proof fuel pump. Capable of handling a wide range of fuels whilst maintaining required safety features of operating in a hazardous area.

It's principle of construction enables refuelling rates up to 80 litre/min

Each unit is certified to:

EEx d IIB T4 ISSEP02 ATEX036.

All of these features ensure that this system is both a reliable & cost effective solution to almost Exd refuelling application.

Specification

Flowrate	80 litre/min
Discharge pressure	1.9 Bar (Max)
Suction lift	5.0m (Max)
Self Priming	2.5m (Max)
Fitting Size	1" BSP(F)
Motor:	230/1/50 EXD
RPM	1450
Current draw	3.5 A
Insulation/Protection	IP55 EExd
Actual weight	14.5Kg

Applications

Class A1i	- Low sulphur diesel
Class A1ii	- Automotive diesel BS2869
Class A2	- Diesel & Gasoil European EN590
Class D	- Derv & Gasoil
EN228	- Unleaded Petrol
Antifreeze	- (undiluted)

Also Available

AG500 EExd

50 litre/min
230/1/50 EExd



AG1500 EEx e

150 litre/min
230/1/50 EEx e

