

Diesel Engine Operated Diesel Fuel Pumps



Diesel Driven Diesel Pump

This range of engine operated centrifugal fuel pumps were designed to meet the growing demand for high flow mobile refuelling applications.

Three sizes of pump are available, all of which are fitted to robust 6.8HP Lombardini diesel powered engines which provide flow rates up to 984 litre/min / 3.6 bar delivery pressure.

Optional trolleys are available in lieu of the powder coated tubular frame which is supplied as standard.

All of these features ensure that this range of fuel pumps are able to meet the demands of almost any high flow transfer application.

Technical Specification

- Self Priming (after initial prime) to 7m
- Max 55°C
- Supplied with removable Camlock Male Spigots
- Optional Trolley
- Optional Bypass

Materials of Construction

- Glass Reinforced Polyester Construction
- Stainless Steel Fasteners
- Buna Seals
- Carbon ~ Ceramic Mechanical Seal
- Polypropylene Cam Lock Fittings

Model	Port Size	Flow Rate (max)	Head (max)	Lift (max)	Weight
DPF25D	50mm / 2" NPT	870 litre/min	25m	7m	45 Kg
DPF26D	50mm / 2" NPT	757 litre/min	36m	7m	45 Kg
DPF35D	80mm / 3" NPT	984 litre/min	25m	7m	48 Kg

Optional Frames

