

Basic Bunded Oil Tanks

PRODUCT OVERVIEW

Entry level Bunded Tank range, which omits the added-value benefits that characterise Harlequin's Advance range of Bunded Tanks.

Fully compliant with all applicable fuel storage requirements and suitable for the storage of Heating Oil, a choice of extra cost fuel storage accessories can be specified upon request.

STANDARD EQUIPMENT

All Harlequin Basic Bunded Tanks are supplied complete with:

- 2" Lockable Fill Point
- 4" Lockable Inspection Point
- Lockable Manhole Access
- 1" BSP (F) Outlet Connection
- Vent
- 32mm Electronic Contents Gauge Fitting Point
- Contents Dipstick
- LRC Failsafe Overfill Prevention Probe

OPTIONAL EQUIPMENT

- Electronic Oil Tank Contents Gauge
- Electronic Oil Tank Contents Gauge c/w Fitting Kit
- Electronic Bund Spillage Detector

INSTALLATION & MAINTENANCE REQUIREMENTS

This product must be installed and maintained by a suitably competent person in accordance with the requirements of:

- British Standard BS5410
- OFTEC Technical Instruction Book 3
- Supplied instructions
- All prevailing statutory requirements e.g. Building Regulations, Environmental Regulations etc.



1300BCT Bunded

NOMINAL CAPACITY:	1,335 litres
LENGTH:	2,100 mm
WIDTH:	950 mm
HEIGHT:	1,540 mm
WEIGHT:	160 kg



1400BCT Bunded

NOMINAL CAPACITY:	1,380 litres
LENGTH:	1,900 mm
WIDTH:	1,250 mm
HEIGHT:	1,420 mm
WEIGHT:	130 kg



1450BCT Bunded

NOMINAL CAPACITY:	1,413 litres
DIAMETER:	1,540 mm
HEIGHT:	1,590 mm
WEIGHT:	105 kg



2000BCT Bunded

NOMINAL CAPACITY:	2,005 litres
LENGTH:	2,360 mm
WIDTH:	1,320 mm
HEIGHT:	1,415 mm
WEIGHT:	180 kg



1000BCT Bunded

NOMINAL CAPACITY:	1,003 litres
LENGTH:	2,150 mm
WIDTH:	710 mm
HEIGHT:	1,420 mm
WEIGHT:	130 kg



1100BCT Bunded

NOMINAL CAPACITY:	1,040 litres
LENGTH:	1,880 mm
WIDTH:	890 mm
HEIGHT:	1,595 mm
WEIGHT:	132 kg



2500BCT Bunded

NOMINAL CAPACITY:	2,442 litres
LENGTH:	2,460 mm
WIDTH:	1,435 mm
HEIGHT:	1,470 mm
WEIGHT:	210 kg